

MONOCHROME CAMERAS

* = MOST POPULAR MODELS

N = NEW MODELS

MODEL	FORMAT	APPLICATION	RES.	LENS MT.	SENSITIVITY	IRIS	POWER	COMMENTS	PREVIOUS
* LTC 0330/21	1/3"	IN/OUTDOOR	380 TVL	CS	.015 FC, .15 LUX	M, A	24 VAC	BLC, general purpose, 4 pin lens connector	TC552A
LTC 0330/21-38	1/3"	IN/OUTDOOR	380 TVL	CS	.015 FC, .15 LUX	M, A	24 VAC	Includes 3.5-8mm Auto Iris Lens	--
LTC 0330/61	1/3"	IN/OUTDOOR	380 TVL	CS	.015 FC, .15 LUX	M, A	120 VAC	BLC, general purpose, 4 pin lens connector	TC551A
* LTC 0350/21	1/3"	IN/OUTDOOR	570 TVL	CS	.01 FC, .1 LUX	M, A	24 VAC	BLC, high resolution, 4 pin lens connector	TC592
LTC 0350/61	1/3"	IN/OUTDOOR	570 TVL	CS	.01 FC, .1 LUX	M, A	120 VAC	BLC, high resolution, 4 pin lens connector	TC591
LTC 0500/20	1/2"	IN/OUTDOOR	570 TVL	C/CS	.0037 FC, .037 LUX	M, A	24 VAC	Ultra-sensitive	--
LTC 0500/60	1/2"	IN/OUTDOOR	570 TVL	C/CS	.0037 FC, .037 LUX	M, A	120 VAC	Ultra-sensitive	--
Mini-Domes									
Note: M=Manual iris support; A=Auto iris support; BLC=Backlight compensation									
* LTC 1142/20	1/3"	INDOOR	380 TVL	--	.03 FC, .3 LUX	--	12 VDC	Clear dome, integral 3.6mm lens, charcoal	--
LTC 1143/20	1/3"	INDOOR	380 TVL	--	.03 FC, .3 LUX	--	12 VDC	Clear dome, integral 6mm lens, charcoal	--
* LTC 1142/21	1/3"	INDOOR	380 TVL	--	.03 FC, .3 LUX	--	12 VDC	Clear dome, integral 3.6mm lens, white	--
LTC 1143/21	1/3"	INDOOR	380 TVL	--	.03 FC, .3 LUX	--	12 VDC	Clear dome, integral 6mm lens, white	--
* LTC 1142/20	1/4"	INDOOR	380 TVL	--	.05 FC, .5 LUX	--	24 VAC	Clear dome, integral 3mm lens, white	--
LTC 1143/20	1/4"	INDOOR	380 TVL	--	.05 FC, .5 LUX	--	24 VAC	Clear dome, integral 6mm lens, white	--
Phortress Domes									
N LTC 1162/20	1/4"	INDOOR	380 TVL	--	.05 FC, .5 LUX	--	24 VAC	Clear dome, integral 3mm lens, white	--
N LTC 1163/20	1/4"	INDOOR	380 TVL	--	.05 FC, .5 LUX	--	24 VAC	Clear dome, integral 6mm lens, white	--
G3 AutoDomes									
(various)	1/3"	IN/OUTDOOR	550 TVL	--	.008 FC, .08 LUX	A	24 & 120VAC	Integrated PTZ dome camera assembly, 6.3"	LTC 0709/20

Note: Refer to G3 AutoDome & EnviroDome datasheets for configurations and models.

COLOR CAMERAS

MODEL	FORMAT	APPLICATION	RES.	LENS MT.	SENSITIVITY	IRIS	POWER	COMMENTS	PREVIOUS
* LTC 0430/21	1/3"	IN/OUTDOOR	330 TVL	CS	.15 FC, 1.5 LUX	M, A	24 VAC	BLC, general purpose, 4 pin lens connector	TC372
LTC 0430/21-38	1/3"	IN/OUTDOOR	330 TVL	CS	.15 FC, 1.5 LUX	M, A	24 VAC	Includes 3.5-8mm Auto Iris Lens	TC372-38
LTC 0430/61	1/3"	IN/OUTDOOR	330 TVL	CS	.15 FC, 1.5 LUX	M, A	120 VAC	BLC, general purpose, 4 pin lens connector	TC371
* LTC 0450/21	1/3"	IN/OUTDOOR	460 TVL	CS	.15 FC, 1.5 LUX	M, A	24 VAC	BLC, high resolution, 4 pin lens connector	TC392
LTC 0450/61	1/3"	IN/OUTDOOR	460 TVL	CS	.15 FC, 1.5 LUX	M, A	120 VAC	BLC, high resolution, 4 pin lens connector	TC391
LTC 0600/20	1/2"	IN/OUTDOOR	480 TVL	C/CS	.037 FC, .37 LUX	M, A	24 VAC	Ultra-sensitive	--
LTC 0600/60	1/2"	IN/OUTDOOR	480 TVL	C/CS	.037 FC, .37 LUX	M, A	120 VAC	Ultra-sensitive	--
Mini-Domes									
Note: M=Manual iris support; A=Auto iris support; BLC=Backlight compensation									
* LTC 1232/20	1/3"	INDOOR	330 TVL	--	.22 FC, 2.2 LUX	--	12 VDC	Clear dome, integral 3.6mm lens, charcoal	--
LTC 1233/20	1/3"	INDOOR	330 TVL	--	.22 FC, 2.2 LUX	--	12 VDC	Clear dome, integral 6mm lens, charcoal	--
* LTC 1232/21	1/3"	INDOOR	330 TVL	--	.22 FC, 2.2 LUX	--	12 VDC	Clear dome, integral 3.6mm lens, white	--
LTC 1233/21	1/3"	INDOOR	330 TVL	--	.22 FC, 2.2 LUX	--	12 VDC	Clear dome, integral 6mm lens, white	--
* LTC 1242/20	1/4"	INDOOR	330 TVL	--	.5 FC, 5 LUX	--	24 VAC	Tinted dome, integral 3mm lens	--
LTC 1243/20	1/4"	INDOOR	330 TVL	--	.5 FC, 5 LUX	--	24 VAC	Tinted dome, integral 6mm lens	--
N LTC 1251/20	1/4"	INDOOR	480 TVL	--	.25 FC, 2.5 LUX	--	24 VAC	Tinted dome, integral 2.5-5.6mm DC iris lens	--
Phortress Domes									
N LTC 1261/20	1/4"	INDOOR	480 TVL	--	.21 FC, 2.1 LUX	--	24 VAC	Clear dome, integral 2.6-5.6mm lens, white	--
N LTC 1262/20	1/4"	INDOOR	330 TVL	--	.5 FC, 5 LUX	--	24 VAC	Clear dome, integral 3mm lens, white	--
N LTC 1263/20	1/4"	INDOOR	330 TVL	--	.5 FC, 5 LUX	--	24 VAC	Clear dome, integral 6mm lens, white	--
G3 AutoDomes									
(various)	1/3"	IN/OUTDOOR	470	--	.08 FC, .8 LUX	A	24 & 120VAC	Integrated PTZ dome camera assembly, 6.3"	LTC 0809/20

Note: Refer to G3 AutoDome & EnviroDome datasheets for configurations and models.

UNITY MONOCHROME CAMERA/LENS/HOUSING/MOUNT

MODEL	FORMAT	APPLICATION	RES.	SUNSHIELD	SENSITIVITY	IRIS	POWER	COMMENTS	PREVIOUS
LTC 7030/20-38	1/3"	INDOOR	380 TVL	--	.027 FC, .27 LUX	A	24 VAC	BLC, Includes 3.5-8mm Auto Iris Lens	--
* LTC 7030/21-55	1/3"	OUTDOOR	380 TVL	INCLUDED	.027 FC, .27 LUX	A	24 VAC	BLC, Includes 5-50mm Auto Iris Lens	--
LTC 7035/20-38	1/3"	INDOOR	570 TVL	--	.018 FC, .18 LUX	A	24 VAC	BLC, high resolution, 3.5-8mm Auto Iris Lens	--
* LTC 7035/20-55	1/3"	OUTDOOR	570 TVL	INCLUDED	.018 FC, .18 LUX	A	24 VAC	BLC, high resolution, 5-50mm Auto Iris Lens	--

Note: A=Auto iris support; BLC=Backlight compensation

UNITY COLOR CAMERA/LENS/HOUSING/MOUNT

MODEL	FORMAT	APPLICATION	RES.	SUNSHIELD	SENSITIVITY	IRIS	POWER	COMMENTS	PREVIOUS
LTC 7040/20-38	1/3"	INDOOR	330 TVL	--	.27 FC, 2.7 LUX	A	24 VAC	BLC, Includes 3.5-8mm Auto Iris Lens	--
* LTC 7040/21-55	1/3"	OUTDOOR	330 TVL	INCLUDED	.27 FC, 2.7 LUX	A	24 VAC	BLC, Includes 5-50mm Auto Iris Lens	--
LTC 7045/20-38	1/3"	INDOOR	460 TVL	--	.27 FC, 2.7 LUX	A	24 VAC	BLC, high resolution, 3.5-8mm Auto Iris Lens	--
* LTC 7045/20-55	1/3"	OUTDOOR	460 TVL	INCLUDED	.27 FC, 2.7 LUX	A	24 VAC	BLC, high resolution, 5-50mm Auto Iris Lens	--

INDOOR CAMERA MOUNTS & HOUSINGS

MODEL	SIZE	STYLE	MAX. CAMERA & LENS	MATERIAL	TAMPER KIT	POWER	COMMENTS	PREVIOUS
* TC9206U	6 INCH	CEILING GRID/WALL	(CAMERA MOUNT)	ALUMINUM/STEEL	--	--	Universal indoor wall/ceiling mount	--
* LTC 9215/00	12 INCH	WALL	(CAMERA MOUNT)	ALUMINUM/STEEL	--	--	Use with cylinder housings, feed-through	--
LTC 9219/01	15 INCH	CEILING-J	(CAMERA MOUNT)	ALUMINUM/STEEL	--	--	Use with cylinder housings, feed-through	--
LTC 9480/00	11 INCH	CYLINDER	7.75 INCH	ALUMINUM	LTC 9080/00	24 VAC	Use with 24 VAC cameras only	LTC 9352/01
* LTC 9483/00	16 INCH	CYLINDER	10.5 INCH	ALUMINUM	LTC 9080/00	--		LTC 9353/00
LTC 9488/00	20.5 INCH	CYLINDER	14 INCH	ALUMINUM	LTC 9080/00	--		LTC 9358/00
TC9345MT7	7 INCH	DOMES	8 INCH	ACRYLIC	--	--	Use with sheet rock or drop ceilings	--
LTC 9312/00	12 INCH	DOMES	8 INCH	ACRYLIC/STEEL	--	--	Use with sheet rock or drop ceilings	--
LTC 9412/00	12 INCH	PENDANT DOME	8 INCH	ACRYLIC/STEEL	--	--		--
LTC 9349/01	6.3 INCH	PLENUM DOME	7.5 INCH	ACRYLIC/ALUMINUM	--	--	Use in plenum ceilings, AutoDome "look"	LTC 9348/00
LTC 9449/00	6.3 INCH	PENDANT DOME	7.5 INCH	ACRYLIC/ALUMINUM	--	--	AutoDome "look", various models	--
LTC 9370/00	10.2 INCH	WEDGE	8 INCH	ACRYLIC/PVC	INTEGRAL	--	2x2 mounting tile: LTC 9070/00	--
TC9375	11 INCH	SURFACE WEDGE	8 INCH	ABS PLASTIC	--	--		--
TC2073	12 INCH	CORNER (CLEAR)	9 INCH	ABS PLASTIC	--	--		--
TC2073T	12 INCH	CORNER (TINTED)	9 INCH	ABS PLASTIC	--	--		--

UNITYDOME MONOCHROME CAM/LENS/HOUSING/MOUNT * = MOST POPULAR MODELS N = NEW MODELS										
	MODEL	FORMAT	APPLICATION	RES.	MOUNTING	SENSITIVITY	STYLE	POWER	COMMENTS	PREVIOUS
N	LTC 9349/20MS-38	1/4"	INDOOR	380 TVL	IN-CEILING	.04 FC, .4 LUX	--	24 VAC	BLC, Includes 3.5-8mm Auto Iris Lens	--
N	LTC 9349/20MS-55	1/4"	INDOOR	380 TVL	IN-CEILING	.04 FC, .4 LUX	--	24 VAC	BLC, Includes 5-50mm Auto Iris Lens	--
N	LTC 9449/20MS-38P	1/4"	INDOOR	380 TVL	PENDANT	.04 FC, .4 LUX	PIPE	24 VAC	BLC, Includes 3.5-8mm Auto Iris Lens	--
N	LTC 9449/20MS-38W	1/4"	INDOOR	380 TVL	PENDANT	.04 FC, .4 LUX	WALL	24 VAC	BLC, Includes 3.5-8mm Auto Iris Lens	--
N	LTC 9449/20MS-55P	1/4"	INDOOR	380 TVL	PENDANT	.04 FC, .4 LUX	PIPE	24 VAC	BLC, Includes 5-50mm Auto Iris Lens	--
N	LTC 9449/20MS-55W	1/4"	INDOOR	380 TVL	PENDANT	.04 FC, .4 LUX	WALL	24 VAC	BLC, Includes 5-50mm Auto Iris Lens	--
N	LTC 9450/20MS-38P	1/4"	OUTDOOR	380 TVL	PENDANT	.04 FC, .4 LUX	PIPE	24 VAC	BLC, Includes 3.5-8mm Auto Iris Lens	--
N	LTC 9450/20MS-38W	1/4"	OUTDOOR	380 TVL	PENDANT	.04 FC, .4 LUX	WALL	24 VAC	BLC, Includes 3.5-8mm Auto Iris Lens	--
N	LTC 9450/20MS-55P	1/4"	OUTDOOR	380 TVL	PENDANT	.04 FC, .4 LUX	PIPE	24 VAC	BLC, Includes 5-50mm Auto Iris Lens	--
N	LTC 9450/20MS-55W	1/4"	OUTDOOR	380 TVL	PENDANT	.04 FC, .4 LUX	WALL	24 VAC	BLC, Includes 5-50mm Auto Iris Lens	--

UNITYDOME COLOR CAM/LENS/HOUSING/MOUNT										
	MODEL	FORMAT	APPLICATION	RES.	MOUNTING	SENSITIVITY	STYLE	POWER	COMMENTS	PREVIOUS
N	LTC 9349/20CS-38	1/4"	INDOOR	330 TVL	IN-CEILING	.4 FC, 4 LUX	--	24 VAC	BLC, Includes 3.5-8mm Auto Iris Lens	--
N	LTC 9349/20CS-55	1/4"	INDOOR	330 TVL	IN-CEILING	.4 FC, 4 LUX	--	24 VAC	BLC, Includes 5-50mm Auto Iris Lens	--
N	LTC 9449/20CS-38P	1/4"	INDOOR	330 TVL	PENDANT	.4 FC, 4 LUX	PIPE	24 VAC	BLC, Includes 3.5-8mm Auto Iris Lens	--
N	LTC 9449/20CS-38W	1/4"	INDOOR	330 TVL	PENDANT	.4 FC, 4 LUX	WALL	24 VAC	BLC, Includes 3.5-8mm Auto Iris Lens	--
N	LTC 9449/20CS-55P	1/4"	INDOOR	330 TVL	PENDANT	.4 FC, 4 LUX	PIPE	24 VAC	BLC, Includes 5-50mm Auto Iris Lens	--
N	LTC 9449/20CS-55W	1/4"	INDOOR	330 TVL	PENDANT	.4 FC, 4 LUX	WALL	24 VAC	BLC, Includes 5-50mm Auto Iris Lens	--
N	LTC 9450/20CS-38P	1/4"	OUTDOOR	330 TVL	PENDANT	.4 FC, 4 LUX	PIPE	24 VAC	BLC, Includes 3.5-8mm Auto Iris Lens	--
N	LTC 9450/20CS-38W	1/4"	OUTDOOR	330 TVL	PENDANT	.4 FC, 4 LUX	WALL	24 VAC	BLC, Includes 3.5-8mm Auto Iris Lens	--
N	LTC 9450/20CS-55P	1/4"	OUTDOOR	330 TVL	PENDANT	.4 FC, 4 LUX	PIPE	24 VAC	BLC, Includes 5-50mm Auto Iris Lens	--
N	LTC 9450/20CS-55W	1/4"	OUTDOOR	330 TVL	PENDANT	.4 FC, 4 LUX	WALL	24 VAC	BLC, Includes 5-50mm Auto Iris Lens	--
N	LTC 9449/20CH-55P	1/4"	INDOOR	480 TVL	PENDANT	.5 FC, 5 LUX	PIPE	24 VAC	BLC, Includes 5-50mm Auto Iris Lens	--
N	LTC 9449/20CH-55W	1/4"	INDOOR	480 TVL	PENDANT	.5 FC, 5 LUX	WALL	24 VAC	BLC, Includes 5-50mm Auto Iris Lens	--
N	LTC 9450/20CH-55P	1/4"	OUTDOOR	480 TVL	PENDANT	.5 FC, 5 LUX	PIPE	24 VAC	BLC, Includes 5-50mm Auto Iris Lens	--
N	LTC 9450/20CH-55W	1/4"	OUTDOOR	480 TVL	PENDANT	.5 FC, 5 LUX	WALL	24 VAC	BLC, Includes 5-50mm Auto Iris Lens	--

OUTDOOR CAMERA MOUNTS & HOUSINGS									
	MODEL	SIZE	STYLE	MAX. CAMERA & LENS	MATERIAL	SUNSHIELD	POWER	COMMENTS	PREVIOUS
	LTC 9215/00	12 INCH	WALL	(CAMERA MOUNT)	ALUMINUM/STEEL	--	--	Use with cylinder housings, feed-through	--
	LTC 9219/01	15 INCH	CEILING-J	(CAMERA MOUNT)	ALUMINUM/STEEL	--	--	Use with cylinder housings, feed-through	--
	LTC 9483/20	16 INCH	CYLINDER	10.5 INCH	ALUMINUM	LTC 9083/00	24 VAC	Includes heater.	TC9383-2
*	LTC 9483/21	16 INCH	CYLINDER	8.5 INCH	ALUMINUM	LTC 9083/00	24 VAC	Includes heater and blower.	--
	LTC 9483/60	16 INCH	CYLINDER	10.5 INCH	ALUMINUM	LTC 9083/00	120 VAC	Includes heater.	TC9383-1
*	LTC 9483/61	16 INCH	CYLINDER	8.5 INCH	ALUMINUM	LTC 9083/00	120 VAC	Includes heater and blower.	--
	LTC 9488/20	20.5 INCH	CYLINDER	14 INCH	ALUMINUM	LTC 9088/00	24 VAC	Includes heater.	TC9388-2
	LTC 9488/21	20.5 INCH	CYLINDER	12.5 INCH	ALUMINUM	LTC 9088/00	24 VAC	Includes heater and blower.	--
	LTC 9488/60	20.5 INCH	CYLINDER	14 INCH	ALUMINUM	LTC 9088/00	120 VAC	Includes heater.	TC9388-1
	LTC 9488/61	20.5 INCH	CYLINDER	12.5 INCH	ALUMINUM	LTC 9088/00	120 VAC	Includes heater and blower.	--
	TC9320	20.5 INCH	PEND. DOME (TINTED)	13 INCH	ACRYLIC/PLASTIC	--	--	Wall mount: TC9320WM	--

CAMERA POWER SUPPLIES (120 VAC INPUT)									
	MODEL	OUTPUTS	POWER PER OUTPUT	ISOLATED	DIMENSIONS (IN.)	WEIGHT	POWER	COMMENTS	PREVIOUS
	TC1323	1	10 VA	--	2Wx1.7Dx2.4H	.53 LB.	24 VAC		--
*	TC1334	1	30 VA	--	2.75Wx2.22Dx3.5H	1.36 LBS.	24 VAC		--
	RT2440SL	1	40 VA	--	2.7Wx2.2Dx3.45H	1.41 LBS.	24 VAC	High power	RT2440
	RTD12/3RT	1	300 mA	--	1.88Wx1.63Dx2.75H	.53 LB.	12 VDC	for Mini-Dome cameras, regulated	--
	LTC 5404/60	4	14.4 VA	NO	7Wx3.5Dx8H	7 LBS.	24 VAC		--
	LTC 5408/60	8	10.5 VA	NO	7Wx3.5Dx8H	7 LBS.	24 VAC		--
	LTC 5416/60	16	10.5 VA	NO	11.25Wx3.5Dx11.25H	10 LBS.	24 VAC		--
	LTC 5414/60	4	12 VA	YES	7Wx3.5Dx8H	9 LBS.	24 VAC	Isolated	--
	LTC 5418/60	8	12 VA	YES	11.25Wx3.5Dx11.25H	12 LBS.	24 VAC	Isolated	--

MONOCHROME MONITORS									
	MODEL	SIZE	WEIGHT	RESOLUTION	DIMENSIONS (IN.)	AUDIO	RACK KIT	COMMENTS	PREVIOUS
*	LTC 2009/61	9 INCH	9.5 LBS.	700 TVL MIN.	8.7Wx9.6Dx9.2H	NO	LTC 9009/00		TC1909A
*	LTC 2012/61	12 INCH	19.6 LBS.	700 TVL MIN.	12Wx12Dx11.3H	NO	LTC 9012/00	Popular mid-size	TC1914A
	LTC 2017/60	17 INCH	33 LBS.	700 TVL MIN.	16.5Wx15Dx15.2H	NO	LTC 9017/00		TC1917
	LTC 2020/90	20 INCH	39 LBS.	700 TVL MIN.	17.5Wx14.96Dx17.4H	YES	n/a		--

COLOR MONITORS									
	MODEL	SIZE	WEIGHT	RESOLUTION	DIMENSIONS (IN.)	AUDIO	RACK KIT	COMMENTS	PREVIOUS
	LTC 2810/90	9 INCH	15.2 LBS.	280 TVL MIN.	10.4Wx13Dx10.2H	YES	LTC 9110/00		--
	LTC 2910/60	9 INCH	15.2 LBS.	280 TVL MIN.	8.8Wx12.5Dx8.9H	NO	TC210AMK	Compact	TC210A
*	LTC 2813/60	13 INCH	20.9 LBS.	320 TVL MIN.	14.5Wx14.75Dx12.2H	NO	LTC 9113/00	Popular mid-size	TC213A
	LTC 2814/90	14 INCH	30.9 LBS.	350 TVL MIN.	13.9Wx15.4Dx13H	YES	LTC 9114/00		LTC 2814/60
N	LTC 2915/90	15 INCH	32 LBS.	560 TVL MIN.	14.3Wx15.1Dx13.7H	YES	LTC 9115/00	High resolution	TC215
	LTC 2917/90	17 INCH	38 LBS.	550 TVL MIN.	15.6Wx16.6Dx13H	YES	LTC 9117/00	High resolution	--
*	LTC 2821/90	20 INCH	33 LBS.	450 TVL MIN.	19.3Wx16.9Dx17.5H	YES	n/a	Economical large monitor	--
	LTC 2921/60	20 INCH	63 LBS.	450 TVL MIN.	18.7Wx18.9Dx16.1H	YES	n/a		TC221
	PA7027C	27 INCH	90 LBS.	680 TVL MIN.	25.7Wx19.6Dx23H	YES	n/a		PA5027C

RECORDERS

MODEL	TYPE	TIME LAPSE	COLOR RES.	B/W RES.	DIMENSIONS (IN.)	FEATURE	RACK KIT	COMMENTS	PREVIOUS
* LTC 3924/61	VHS	6,18,30hr	300 TVL	350 TVL	17.1Wx14.4Dx3.7H	1,2,5	LTC 9061/00	<i>Most popular</i>	LTC 3924/60
* LTC 3963/61	VHS	6-240hr	300 TVL	350 TVL	17.1Wx14.4Dx3.7H	1,2,4,5	LTC 9061/00		LTC 3963/60
LTC 3991/60	SVHS	2-720hr	400 TVL	400 TVL	17.1Wx14.4Dx3.7H	1,2,3,4,5	LTC 9061/00	<i>Premium</i>	TC3991
LTC 3995/60	DIGITAL	18min-1152hr	440 TVL	440 TVL	17Wx1.48Dx1.7H	1,2,3,4	INCLUDED	<i>Digital, internal 4.3 GB hard drive</i>	--

Note: Feature key: 1=even record selection; 2=high speed alarm search; 3=time/date search; 4=RS-232 input; 5=high-density recording.

All Philips CSS VHS & SVHS Recorders include automatic head cleaner, program timer, and time/date generator.

LTC 3924/61, LTC 3963/61 and TC3991/60 models support 24 hour "real time" high density mode when used with T-160 tapes.

DIGITAL MOTION DETECTORS

MODEL	IN/OUT	APPLICATION	ZONE SIZE	ZONES	DIRECTION/SPEED	LOOPING	RACK KIT	COMMENTS	PREVIOUS
* LTC 2210/60	1/1	INDOOR	64Hx30V	8	NO	YES	LTC 9101/00	<i>Basic single camera</i>	TC8210
LTC 2211/60	4/2	IN/OUTDOOR	40Hx30V	4/CAM	YES	YES	LTC 9101/00		TC8211
LTC 2212/60	8/2	IN/OUTDOOR	40Hx30V	4/CAM	YES	YES	LTC 9101/00		TC8212

MONOCHROME QUAD DISPLAYS

* = MOST POPULAR MODELS

N = NEW MODELS

MODEL	IN/OUT	FULL SCREEN	ALARMS	FREEZE	DIGITAL MEMORY	LOOPING	RACK KIT	COMMENTS	PREVIOUS
LTC 2372/60	4/1	NO	NO	NO	8 BIT, 512Hx484V	NO	LTC 9101/00	<i>Basic quad</i>	LTC 2272/60
* LTC 2376/60	4/2	YES	YES	YES	8 BIT, 512Hx484V	YES	LTC 9101/00		LTC 2276/60

COLOR QUAD DISPLAYS

MODEL	IN/OUT	FULL SCREEN	ALARMS	FREEZE	DIGITAL MEMORY	LOOPING	RACK KIT	COMMENTS	PREVIOUS
LTC 2375/60	4/1	NO	NO	NO	16 BIT, 1024Hx1024V	NO	LTC 9101/00	<i>Basic quad</i>	TC8275
* LTC 2377/60	4/2	YES	YES	YES	16 BIT, 1024Hx1024V	YES	LTC 9101/00		TC8277

UNIVERSAL (MONOCHROME & COLOR) MULTIPLEXERS

MODEL	IN/OUT	ACTIVITY DET.	ALARMS	MODE	DIGITAL MEMORY	LOOPING	RACK KIT	COMMENTS	PREVIOUS
N LTC 2642/90	9/2	YES	YES	DUPLEX	720Hx484V	YES	INCLUDED	<i>Duplex: record and view all cameras</i>	LTC 2642/60
N LTC 2662/90	16/2	YES	YES	DUPLEX	720Hx484V	YES	INCLUDED	<i>Duplex: record and view all cameras</i>	LTC 2662/60

All multiplexers have integral rack mounting ears.

UNIVERSAL (MONOCHROME & COLOR) MULTIPLEXER CONTROL SYSTEMS

MODEL	IN/OUT	VCR CONTROL	ALARMS	MODE	PREPOSITIONS	CODE OUT	LOOPING	COMMENTS	PREVIOUS
N LTC 2622/90	6/2	NO	YES	DUPLEX	99/CAMERA	4	YES	<i>Duplex: record and view all cameras</i>	LTC 2622/60
N LTC 2672/90	9/2	YES	YES	TRIPLEX	99/CAMERA	5	YES	<i>Triplex: record, playback and view all cameras</i>	LTC 2672/60
N LTC 2682/90	16/2	YES	YES	TRIPLEX	99/CAMERA	5	YES	<i>Triplex: record, playback and view all cameras</i>	LTC 2682/60

All multiplexer control systems have integral rack mounting ears.

PAN-TILT-ZOOM CAMERA CONTROLLERS

MODEL	BIPHASE	MAX. PAN/TILT	PREPOSITIONS	HARDWIRE	TOUR	RACK KIT	COMMENTS	PREVIOUS
LTC 5133/60	NO	1	NONE	YES, 120 VAC	NO	LTC 9101/00		TC6135
LTC 5134/60	NO	1	NONE	YES, 24 VAC	NO	LTC 9101/00		TC6135-24
* LTC 5136/60	YES	8	99/CAMERA	NO	YES	--	<i>One BiPhase code output</i>	--
LTC 5138/60	YES	1	99/CAMERA	NO	YES	--	<i>Requires PC, "Virtual Keyboard"</i>	--

SEQUENTIAL SWITCHERS

MODEL	IN/OUT	CAN SATELLITE	ALARMS	DWELL	LTC 5135/60 COMP.	LOOPING	RACK KIT	COMMENTS	PREVIOUS
LTC 5121/60	2/1	NO	NO	2-45 SEC.	NO	NO	LTC 9101/00		TC8121
* LTC 5141/60	4/1	NO	NO	2-45 SEC.	NO	NO	LTC 9101/00		TC8141
LTC 5104/60	4/1	NO	YES	1-64 SEC.	YES	YES	LTC 9101/00		TC8104C
* LTC 5108/60	8/2	NO	YES	1-64 SEC.	YES	YES	LTC 9101/00		TC8108C

MATRIX SWITCHERS

MODEL	IN/OUT	MAX. IN/OUT	GUI COMP.	ALARMS	MAX. KEYBOARDS	CODE OUT	LOOPING?	COMMENTS	PREVIOUS
LTC 8100/60	8/2	8/2	YES	8	2	8	YES	<i>Non-expandable.</i>	--
LTC 8200/60	16/5	16/5	YES	16	4	12	YES	<i>Non-expandable.</i>	--
* LTC 8300/60	32/6	32/6	YES	32	4	16	YES	<i>Non-expandable.</i>	LTC 8301/60
LTC 8500	--	64/8	NO	64	8	32 OR 64	NO	<i>Expandable with input & output cards.</i>	TC8500
* LTC 8600	--	128/16	YES	128	16	32 OR 64	YES	<i>Expandable with input & output cards.</i>	TC8600
LTC 8800	--	256/64	YES	256	32	32 OR 64	YES	<i>Expandable with input & output cards.</i>	TC8800
LTC 8900	--	4096/512	YES	1024	64	32 OR 64	YES	<i>Expandable with input & output cards.</i>	--

Note: Maximum inputs/outputs is non-satellited. Higher numbers of alarm inputs require additional accessories.

Keyboards are sold separately.

All matrix switchers have integral rack mounting ears.